

DECLARATION OF PERFORMANCE

DoP Reference number: - **NL-MDFDoPv7**

West Fraser Europe Ltd

Station Road

Cowie

Stirling

FK7 7BQ

Unique identification code of the product type	Intended use	Systems of AVCP	Notified Body	Harmonised standard
L-MDF >9mm to 45mm*	Internal use as non-structural components in dry conditions	4	Not Applicable	EN13986:2004 +A1:2015
*The unique identification of the product-type is a combination of the technical class and the individual product's nominal thickness				

Declared performance (covering a range of product-types L-MDF >9mm to 45mm*)

Essential characteristics	Performance			
	>9 to 12	>12 to 19	>19 to 30	>30 to 45
Thickness (mm)				
¹ Water vapour permeability μ	NPD	NPD	NPD	NPD
Release of formaldehyde	E1	E1	E1	E1
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm
² Airborne sound insulation (surface mass) R (dB)	NPD	NPD	NPD	NPD
³ Sound absorption Frequency range 250Hz to 500Hz (α)	0.1	0.1	0.1	0.1
³ Sound absorption Frequency range 1000Hz to 2000Hz (α)	0.2	0.2	0.2	0.2
⁴ Thermal conductivity λ (W/m.K)	NPD	NPD	NPD	NPD
Air Permeability V_0 (m ³ /h)	NPD	NPD	NPD	NPD
Durability				
Internal bond (N/mm ²)	0.45	0.45	0.45	0.40
Swelling in thickness (%)	16	14	12	11
Biological	Use Class 1			

⁵ Reaction to fire (see notes to table for field of application details and associated documentation references)		Minimum thickness	Class (excluding floorings) ^g	Class (Flooring) ^h
	Without an air gap behind the panel <small>abef</small>	9	D-s2,d0	D _{fl} ,s1
	With a closed or open air gap ≤ 22mm behind the panel <small>cef</small>	9	D-s2,d2	-
	Closed air gap behind the panel <small>def</small>	15	D-s2,d0	D _{fl} ,s1
	With an open air gap behind the panel <small>def</small>	18	D-s2,d0	D _{fl} ,s1
	Any end use <small>ef</small>	3	E	E _{fl}
a Mounted without an air gap directly against class A1 or A2-s1, d0 products with minimum density 10kg/m ³ or at least class D-s2, d2 products with minimum density 400 kg/m ³ . b A substrate of cellulose insulation material of at least class E may be included if mounted directly against the wood-based panel, but not for floorings. c Mounted with an air gap behind. The reverse face of the cavity shall be at least class A2-s1, d0 products with minimum density 10 kg/m ³ . d Mounted with an air gap behind. The reverse face of the cavity shall be at least class D-s2, d2 products with minimum density 400 kg/m ³ . e Veneered, phenol- and melamine-faced panels are included for class excl. floorings. f A vapour barrier with a thickness up to 0,4 mm and a mass up to 200 g/m ² can be mounted in between the wood-based panel and a substrate if there are no air gaps in between. g Class Provided for in Table 1 of the Annex to decision 2000/147/EC h Class Provided for in Table 2 of the Annex to decision 2000/147/EC				

NOTES TO TABLE

- 1 Taken from Table 9 of EN 13986:2004+A1
- 2 Calculated according to clause 5.10 of EN 13986:2004+A1
- 3 Taken from Table 10 of EN 13986:2004+A1
- 4 Taken from Table 11 of EN 13986:2004+A1
- 5 reaction to fire classes from Table 1 of Commission Decision 2003/43/EC of January 2003 (OJEU L13 of 18.1.2003) corrected by Corrigendum (OJEU L33 of 8.2.2003) and amended by Commission decision 2007/348/EC of May 2007 (OJEU L131 of 23-05-2007); also reproduced in Table 8 of EN 13986:2004+A1:2015 for wood-based panels installed according to CEN/TR 12872

The performance of the product identified is in conformity with the declared performance.

This declaration of performance is issued in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

John Robb

At: - Cowie, Scotland

On: - 03-07-2023