

CaberFloor P5 particleboard with an acoustic layer to reduce sound transmission.

- Available as 18mm or 22mm CaberFloor P5 with a 10mm sound reducing layer
- Reduces impact sound transmission by $\Delta L_w 19dB^*$
- Contributes to airborne noise reduction†
- Use D3 PVA in the joints
- To be overlaid onto an existing deck
- Use in conjunction with flanking strip
- Made in the UK, using eco recycled felt

* 19dB sound reduction applies when CaberAcoustic is installed on its own. Greater reductions applicable (see table) when used within a system for noise transference reduction.

† When used in the right system.

Suitable for

- Dry domestic
- Domestic new build
- Refurbishment
- Commercial**

** Suitable for commercial use in 22mm only

CaberAcoustic is available in

Thickness mm	Length mm	Width mm	Edge profile	Sheets per pack
28***	2400	600	TG4	100
32***	2400	600	TG4	82

***Including 10mm acoustic layer

CaberAcoustic performance

	28mm***	32mm***
Impact $L'_{nT,w}$ dB	54	52
Airborne $D_{nT,w}$ dB	60	58
Airborne $D_{nT,w} + C_{tr}$ dB	54	53



Installation instructions



CaberAcoustic conforms with:



Our CaberFloor range:

- CaberFloor P5
- CaberDek
- CaberAcoustic
- **Adhesives**
 - CaberFix D4
 - CaberFix Joint&Joist
- **Tapes**
 - CaberFix Tape

enquiries.uk@westfraser.com | 01786 819 225 | CaberFloor.com



West Fraser

SterlingOSB® Zero
Strength you can build on

CaberFloor®
Systems you can trust

CaberMDF®
The professional's range